



2500 South Meridian • Oklahoma City, OK 73108-1744
Office: 405-681-6691 • Toll Free: 800-965-7677 • Fax: 405-681-6693

DISTRIBUTORS OF **BLUE BIRD** SCHOOL BUSES

Corporate Office
Ryan Ross, General Manager

Oklahoma Bus Sales
Ryan Ross, Sales Representative

Customer: Ada City Public Schools
ADDRESS: 324 W. 20th Street
CITY/STATE/ZIP: Ada, Oklahoma 74820

CONTACT: Mr. Jonathan Boeck Trans. Dir.
TELEPHONE: 580-310-7359
BID DUE DATE: Immediate

General Description:

2026 Model Year: Micro Bird by Girardin, Type-A Multi-function School Bus (MFSAB), Series: G5

Capacity: 14-Passenger in HSM High-back, STD School Bus Bench Seating

Make: Micro Bird by Girardin
Model: G5 Series, 139" Wheelbase (Dual Wheel), (14) Passenger Capacity w/ Wheel-wells, (4) Rows, 12,300lb GVWR

----- Body Specifications: -----

Air Conditioning:	Dash (Chevrolet/OEM) + 53K Rear AC System: 68K Total BTU A/C w/ Skirt Mounted Condenser and 2 nd Compressor
Back-Up Alarm:	112DBA, Safety Horn SAE-operates in reverse gear
Bumper:	Pressed Steel Channel (10" x 3/16") Flanged 2" Top/Bottom w/ 1" Square Tubing Reinforcement
Child Reminder:	Child Check System, Dome Lights Warning, Entrance Door Activated
Entrance Door:	<u>Double-Out Electric Entrance Door:</u> Clear Glass (Non-Tinted), 32" Wide (10 year, 200,000-cycle tested) Grey Head Pads above All Doors (2) Step Step-well with Ribbed Covered Steps (Gray) Driver's Step Below Driver's Door Rear Door Center Mounted with Upper/Lower Glass (tint 26% light transmittance) Retainer RR Emergency Door RR Door Latch/Slide Bar/ 3PT w/ Ajar Buzzer Vandalock: Interlock Rear Emergency Door
Exit:	Roof Hatch; Spheres Push-out Windows: 1 Per side - 2 Per Body (Black Frame)
Emergency Exit:	Grey Zenith (Ribbed Isle with White Nosing) (Smooth Under Seat) Plywood Flooring: 1/2" Treated Floor Steel-14ga
Floor Covering:	Injection plastic, installed on lower FRT sections of each body side, 12"H, flanged 3 3/4" under body 76" @ Center Isle
Gravel Shield:	FRT Heater & Defroster (Chevrolet/OEM)
Head Room:	Rear Under Seat: 42,000 BTU
Heaters:	Defroster Fan: RH mounted above windshield (2 Speed) Heater Valve Bleeder & Shut Off Valve Cable Under Body (Manual)
Insulation:	1 1/2" thick fiberglass in the headlining, Side, FRT and Rear walls (Includes roof bows)
Lights: Back-up Lights: (2) White, Recessed 4" LED Clearance Lights/Marker: (2) Red Rear & (2) Amber FRT, Recessed LED, combination side marker/clearance lamps Directional Lights: FRT (Chevrolet/OEM) / Rear turn signals: (2) Recessed, 7" amber LED Directional Lights (Side): Amber LED w/ armor Dome Lights: (4) in Roof Skin Identification Lights: (3) Recessed, Red LED -Rear Cap / (3) Recessed, Amber LED - FRT Cap Step-well Light: Interior, LED Stop & tail: (2) Recessed 7" Red stop/tail LED / (2) Recessed, 4" Red stop/tail, LED Exterior Light: Entrance Door - LED License Plate Light: LED	

Wiring System: STD G5 w/ Solenoid

Mirrors: **Exterior: Heated & Remote** Rearview- Rosco Accustyle w/ **EZ & Heated** Cross view -"Mini-Hawkeye"
Interior: 6x16 Flat Mirror, Padded edged, [REDACTED]

Mud Flaps: FRT & Rear Mud Flaps

Paint: **Exterior: Oxford White**
Note: Chassis was original OEM Yellow at GM, but painted white at Micro Bird.
Exterior Roof: White
Interior: White w/ Grey Trim

Radio: **AM/FM/MP3** (Chevrolet/OEM) w/ (4) Speakers

Reflective Tape: 2" Reflective tape: (White) Rear Perimeter & Sides Rear / Emergency Door: Decal+ Tape Push/Out, (White) 1"

Rub Rails: Floor, Seat, Skirt

Safety Equipment: 5lb fire extinguisher, First Aid Kit Oklahoma Spec, Body Fluid Clean-up Kit, (3) Triangle Warning Devices, Seat Belt Cutter

[REDACTED] - No Seat Belts Installed or Implied
(Review Floor Plan for Seat Size and Placement)

Barriers: DOT Approved Barriers 39" LH&RH Grey Fire block, High Back w/ RH Kick Panel and 1.25" LH Stainless Steel Grab Rail

Driver's Seat: Vinyl (Chevrolet/OEM) w/ Aisle Side Arm Rest and **Orange Seat Belt**

Static Roof Vent: Non-closing static roof vent

Switches: Rocker - Type, w/ Pilot light integrated into each switch, back lighted (includes Noise Suppression Switch)

Undercoating: MIL-C-62218-92 rev A Certified Rust Proofing and Salt resistant, Full Body Undercoating

Windows: Side: tint 26% light transmittance, w/ 2 Push-out windows (1) per side, Black framed
Rear: tint 26% light transmittance
More-view™ 551In² of unobstructed glass area (between A-Pillar and Entrance Door)

Windshield: (Chevrolet/OEM)

Windshield Wipers: Variable Speed, Intermittent (Chevrolet/OEM)

Windshield Washer: (Chevrolet/OEM)

Body Construction:

Main Structure: assembled with AVDEL fasteners & structural rivets. Only FRT and Rear structures may be welded.

Body Structure: One Piece roof bows, floor-to-floor, hat section type, 16-gauge galvanized steel w/ (2) 18-ga roll formed structural beams extended full length of bus

Side Impact Barriers: Reinforced side impact barriers, galvanized steel, riveted to sub-floor. 3/16" thick L-shaped reinforcement integrated into seat rail

Exterior Side Panels: 18-ga pre-primed aluminum **Exterior Rear Panels:** One-Piece Fiberglass reinforced composite panel w/ waterproof recessed lights

Roof Panels: One Piece 18-ga aluminum, drip rail incorporated immediately above side windows

FRT and Rear End Structure: steel square tubing, mechanically affixed to sub-floor and roof bows.

Exterior Rear Wheel Trim: Wheel trim on each side of bus over the rear wheels. 1/8" thick high-quality injection plastic

-Specifications subject to change without prior notice.

Chassis Specifications:

Make: Chevrolet

Model #: GR 1WT Model 3500

Alternator:

GVWR / Suspension:

Rear GAWR:

FRT GAWR:

Rear Axle Ratio:

Body Mounts:

Batteries:

Brake System:

Bumper (Front):

Chassis Prep:

Cruise / Speed Control:

Drive Line:

Engine:

Exhaust System:

Fuel Tank:

Gauges:

Headlights:

Horn:

Steering:

Tire and Wheels:

Wheels:

Transmission:

Tow Hooks:

Wheelbase:

Single 220amp (OEM Chevrolet)

12,300lb GVWR rating / Suspension: FRT: Independent / Rear: Multi-leaf

8600lbs

4300lbs

3.73

Chevrolet OEM Body Mount Cushions (Pucks)

Dual Isolated Batteries: Aux battery contained in box w/ Sliding Tray

4 Wheel Disc Type w/ ABS & Brake Warning Indicator

Chevrolet OEM Painted Black

School Bus Chassis Prep Package- Chevrolet (OEM)

Chevrolet (OEM) Provided

Guard FRT

6.6L Gasoline V8

Single horizontal pipe, aluminized steel, Relocated to the LH Side

32 gallon

Speedometer, Voltmeter, Oil pressure, Engine temp., Fuel gauge

(OEM) Chevrolet, Daytime Running Lamps

(OEM) Chevrolet Dual Electric

Tilt Steering, Driver's Air Bag w/ Power Steering

FRT and Rear: LT225/75R16-E Tubeless Radials, Highway Tread

16"x6 Steel Rims - Stainless Steel Wheel Liners Included

8 Speed Automatic HD

Rear

139"

Primary Warranty Terms and Conditions:

Chassis: Chevrolet Limited Warranty: Three (3) year/ 36,000 mile Basic & Five (5) year / 60,000 mile Power Train**

Micro Bird Body Warranty: Five (5) Year / 100,000 mile Limited Warranty: Body Structure, Seat Frame and Barrier Frames**
One (1) Year / 12,000 mile Limited Warranty: Body Parts, Accessories and Components, except those having their own separate warranty**

ACC Climate Control Warranty: Two (2) Year Unlimited / Three (3) year / 75, 000 mile Limited warranty**

**** Please review official factory warranty documentation for Terms and Conditions.**
**** Ross Transportation is not responsible for OEM factory (Micro Bird, Chevrolet & ACC Climate) changes and conditions in warranty policy.**
**** For Reference Purposes Only**

TOTAL UNIT COST, FOB: School_____

\$ 2,332.00, per unit

Note: One (1) unit left in stock. Bid subject to prior sale.

ESTIMATED DELIVERY TIME: _____

150 - 180 Days Upon PO

Note: Estimated Delivery date based on factory information as of 07/07/2026 and is subject to change without prior notice.

Optional Equipment for School Consideration: (Not Factored Into Above Bid Pricing):

Gatekeeper Digital w/ Three W/A Interior Lens: _____ **\$2,275.00 additional, per bus**

Ryan Ross_____
Ross Transportation, Inc.

Bid Accepted by School District Official

07/07/2026_____
Date of Bid:

Date of Acceptance:

Holt Truck Centers	
DH500 - 14P Non-CDL Activity Bus	
Total Cost: \$106,931.00 per unit	
Delivery: Approx. 60 days from receipt of purchase order	
QTY	DESCRIPTION
1	Graphics to match activity bus fleet
1	Gatekeeper camera system with three wide angle lenses
1	Spec, FMVSS "Multifunction School Activity Bus", meets all "School Bus" FMVSS except traffic control, >10,000# GVWR, driver plus 10 or more passengers (W/C counted as 4 pax), may be used to transport students between school and places other than home.
1	Core components, DRW high headroom model 5 section. Standard floor (with wheelwells), 76" interior headroom, 25"X78" entrance door, 96" overall width, all-galvanized-steel construction. Body fully insulated.
1	Chassis Ford-US/2026/DRW 158 E350/7.3Eco/12500/White/AC/Tilt/Cruise/Drivers Seat Standard/ALT. STD/OEM RADIO/Standard Differential/White Wheels/Black Bumper/Fast Idle/No Block Heater/No Spare Tire/No Speed Governor/Standard Battery
1	A/C 70K, dual compressor, 2 fan, skirt mount condenser, dash & in-wall evaporator, Ford 7.3G.
1	Battery tie-in for Ford gas units. 2 batteries held in a battery box. Adds second battery.
1	Bumper 10" x 3/16 galvanized steel channel DRW, wrap around extending forward at least 12" with protecting end caps, for use with exhaust pipe routed under the bumper or to the side.
1	Bumper Brace to attach to frame side, DH 400/500 and DE/DH 416 models, all Gas and Diesel exhaust systems.
1	Fuel system protection and preparation for Ford gas standard or elevated floor 138"/158"WB DRW
1	Tow eyes rear only, installed on chassis frame
1	Fuel sending unit access cover, black diamond tread plate recessed into rubber floor to provide inspection access to fuel sending unit.
1	Door, entrance, black aluminum frame with full-length tempered AS2 glass for SH/DH units
1	Door entrance control, electric mechanism above door header, for glass doors, driver control panel mounted in doghouse. No manual cable-release.
1	Rear egress door, RH (curbside) hinge, Steel construction, select glass rear door upper/lower separately.
1	Rear door hinge continuous stainless steel
1	Rear Door Latch single latch at center of door, with interior red handle and exterior web style non-hitching handle.
1	Backup-alarm 112dBA that is activated upon placing the bus in reverse gear, wired through the ignition.

1	Switch for heater & fan shutdown, quickly limits interior noise, includes AM/FM radio, heater, defroster, and A/C. Does not affect windshield wipers.
1	Child alert system. None.
1	Backup camera safety system with 7" Monitor in the rearview mirror. Rosco
1	Ford 500/516 exhaust under the rear bumper gasoline
1	Endcaps fiberglass front and rear exterior for use without warning lights on DH commercial/MFSAB units
1	Exterior steel rear corner skins left and right, driprail and below emergency exit rear door for DH units
1	Exterior aluminum left and right roof skins for DRW 500 (5section) units
1	Exterior steel left and right side skins, behind and above driver skins for DH 500 (5section) units
1	Skirts, steel below body panels for std floor DH500
1	Storage/Battery Box, steel skirt with additional steel compartment
1	Mud Flaps Rear DH
1	Entrance step drives side, Ford, bright aluminum diamond tread, includes flat mud flap on passenger side.
1	Flooring black rubber, 1/8" smooth rubber under seats, 3/16" ribbed center aisle rubber 15" wide.
1	Flooring step treads, DRW standard and elevated floor models, black ribbed tread with integral white ribbed nosing.
1	Plywood subfloor for DH/E500 units, 1/2" thick
1	Cover tops and sides of interior wheel well with black elastomer trim cover, fits dual rear wheel wheelwells
1	Heater 60K floor mount for Ford units placed IN RIGHT HAND REAR CORNER OF BUS, for gas engines, includes 2 shutoff valves, BLEEDER VALVE
1	Heater shut off valve, cable operated with cable operator located on the dash, use with Ford units only.
1	Interior panels below window, embossed aluminum, standard floor 500 units.
1	Interior Panels Rear Wall DRW with Exit Door, with AC cutout.
1	Interior panels upper, smooth aluminum painted white for DRW 500 units.
1	Grabrail 42" long 1 1/4 dia. stainless, mounted left of entry on RH barrier, designed to prevent entanglement (Passes NHSTA string and nut test)
1	Grabrail 30" long 1 1/4 dia. stainless, mounted right of entry, designed to prevent entanglement (Passes NHSTA string and nut test)
1	Mirror interior clear view back bonded glass, rounded corners and protected edges, 6 x 30 flat. Installed above drivers head on front bulkhead. Interior mirror providing the driver a clear view of interior and rear exit door.
1	Vandal lock for Ford E-S, permits manual lock of rear emergency door from inside while bus not in use, with buzzer and visual indicator on panel. Engine will not start until lock is disengaged, warning buzzer will activate to alert driver lock is engaged.

1	Brake/tail lights LED with separate LED license plate light, (2) 4" flush mount
1	brake/tail lights, 2- 7" LED type
1	Clearance lights LED type; row of three red lights on rear of bus and single reds on left & right rear, row of three amber lights on front of bus with single ambers on left and right front sides. Lights are low profile grommet mount.
1	Four domelights are powered through the ignition, will only function when ignition is turned on and dome light switch is on.
1	Drivers dome light tied to OEM drivers door open circuit, comes on when drivers door is open, will time itself out when door is shut.
1	Lamps, turn signal amber LED rear 7"
1	Lamps, backup white (2) 4" flush mount LED
1	Lights, stepwell lights are wired ignition hot and are illuminated whenever the DOD is opened.
1	Strobe light, roof mounted, low profile, dual flash, with switch. Power off ignition. Strobe located 1' from rear of bus.
1	Warning lamps, none
1	Electrical control panel for buses with no 4 or 8 light system.
1	Lights, turn signal, amber LED 2" below side bodyrail and behind entrance doors. Mount with armor.
1	Remote Heated Rearview and Crossview mirror system w/ black bracketry for Ford DRW buses. ROSCO AccuStyle 8"x15" dual Rearview mirror incl. 7"x9.5" flat and 7"x4" convex mirror glass, with Heated EyeMax LP Crossview mirrors.
1	Headknockers to comply with FMVSS 222; foam pads covered with gray fire block upholstery.
1	Paint body exterior white, Ford DH/DE buses.
1	Radio, OEM supplied, 4 speakers. Provides tie-in harness to main chassis.
1	Rubrails, floor level side rubrails , 4.6" tall X 16 ga steel.
1	Rubrails, seat level side rubrails that wrap around the rear of the bus to the emergency door, 4.6" tall X 16 ga steel.
1	Rubrails, window level side rubrails , 4.6" tall X 16 ga steel.-
1	Skirt level rubrails, for use with 500 models
4	Rubrails painted white color.
1	Triangle warning reflectors (set of three).
1	Fire extinguisher, 5 lb., 3A 40BC with 10" hose and nozzle,, may only be mounted near entrance door.
1	Seat belt cutter, loaded loose in driver compartment.
1	Body fluids kit for AL, AR, CO, CT, KS, MA, MN, MO, ND, PA, SD, WI, WY, WV
1	First aid kit 24 Unit for AK, AL, AR, AZ, CT, DE, FL, GA, IA, ID, IL, IN, KS, KY, LA, MA, ME, MI, MN, MO, MS, MT, NC, ND, NE, NH, NJ, NM, NV, ,OH, OK, PA, RI, SC, SD, TN, TX, UT, VT, WA, WV, WY
1	Barrier, 37" left hand high back with medium gray fire block upholstery, leg at 27" position, for 36" & 39" seat. IMMI

1	Barrier spacing LH to B-pillar, spacing provides energy absorption zone for 2 passengers per FMVSS222 with barrier placed behind B-pillar, must be selected when LH front seat accommodates 2 passengers.
1	Barrier, 37" right hand high back with medium gray fire block upholstery, no welting, leg at 27" position, for 36" & 39" seat. IMMI
1	Barrier spacing RH to stepwell, none.
3	Seat, 36" left hand, IMMI SABRE two passenger without lap belts, with medium gray fireblock upholstery, no welting. Leg at 27" position.
3	Seat spacing LH 28in hip/knee, maximum allowable to meet FMVSS 222 (school bus certification).
4	Seat, 36" right hand, IMMI SABRE two passenger without lap belts, with medium gray fireblock upholstery, no welting. Leg at 27" position.
4	Seat spacing RH 28in hip/knee, maximum allowable to meet FMVSS 222 (school bus certification).
7	Seat mounting hardware floor mount seats, required for each non-track-mount seat
1	Tape, reflective two inch white, outline sides/rear of DH/DE units
1	Signage, identification, "Collins"
1	Exterior decal 2" tall "EMERGENCY DOOR" in black/arrow in red. Interior decal 2" tall "EMERGENCY DOOR" in red/arrow in red.
1	Wheel covers stainless steel Ford DRW
1	No Stop Arm
1	Auxiliary fan two-speed, right side over windshield.
1	Roof vent, static with control grille.
1	Roof Hatch Transpec Low Profile Standard Safety Vent II Model 1975, 1" White Tape on Ext. Perimeter, Activate Buzzer when Opened w/ Ignition on, Emergency Exit Decals, Operating Instructions, Interior & Exterior Handles, Not Approved for Canada
1	Window Transition Ford glass, AS2 tempered clear glass
1	Windows Rear Body with Rubber Mounted AS3 Tempered 32% Tinted Glass
1	Window Rear Door Lower Rubber Mounted AS3 Tempered 32% Tinted Glass
1	Window Rear Door Upper Rubber Mounted AS3 Tempered 32% Tinted Glass
10	Window Split Sash 36" with AS3 Tempered 26% Tinted Glass, providing an unobstructed 12 x 28 opening when upper sash is lowered.
1	Window Split Sash 36" RH and LH Vertical Egress Hinge, Release Handle, Buzzer, Interior/Exterior Signage, and White Exterior Reflective Tape.
1	Core electrical items for Ford buses with minimal option content except Transit. Includes Elect. Board, switch panel, buzzer, domes, step lights, and main harness
1	Undercoat body components, chassis components such as driveline, brake lines, wiring, exhaust system are not undercoated.

1	Warranty, extended limited body, covers body shell, structure, seat structure for 5 YR/100K MI, manufacturer's components for 3 YR/36K MI, other components 3 YR/36K MI. Excludes corrosion due to road chemicals. See warranty policy for full details.
---	--